

ed by Paper Multi Coatings (S) Pte Ltd 30 Loyang Way, #02-18, Singapore 5087

Technical Facts

	SK Multi-Floor	SK EPO Floor	SK Roadline
Mixing Ratio	_	4 part resin (Part A) to 1 part cure (Part B) resin and hardener to be mixed thoroughly prior to application	_
Coverage	1) Flat Finish Approx. 0.30 - o.40kg/m²	Approx. 5.50sq.m/litre @100 microns	Approx. 6.00sq.m/litre @100 microns
Drying time	At 30% Touch Dry - 30 minutes Hard Dry - 3 hours	At 30° C Touch Dry - 2 hours Hard Dry - 8 hours	At 30° C Touch Dry ~ 2 hours Hard Dry ~ 2 -4 hours
Recommended coats	2 costs	2 coats	2 coats
Standard Packing	5 kg per set	5 liters per set	5 liters per can

Directions for Use

- 1. Prepare the surfaces by carefully removing all foreign substances.
- 2. Apply two (2) coats of Multi-Floor/ SK EPO Floor. (Optional) Mix Multi-Floor with sand for anti-slip finish.



Company Information

Japan Head Office 日本

Japan (Headquarters) SK Kaken Co. Ltd.

5-25, 3-Chome, Nakahozumi, Ibaraki City, Osaka, 567-0034 Japan. Tel: (81-721)-21-7727 Fax: (81-726)-21-7728

Malaysia 马来西亚

Manufactured by

SKK Chemical (M) Sdn. Bhd

No. 7, Jalan Sepadu 25 / 123, Seksyen 25, Taman Perindustrian Axis, 40400 Shah Alam Selangor Darul Ehsan, Malaysia. Tel: (603) 5122 4800 Fax: (603) 5122 4808 Website: www.skk.com.mv

Singapore 新加坡

SKK (S) Pte. Ltd.

No. 14, Pandan Road, Singapore 609262. Tel: (65) 6274 0020 Fax: (65) 6278 0060

Hong Kong 香港

SKK (HK) Co. Ltd.

Suites 1007-1010, 101F, Pah Sing Financial Centre, 108, Gloucester Road, Wanchai, Hong Kong. Tel: 852-2529-3968 Fax: 852-2527-0299

Korea 韩国

SK Kaken (Korea) Co. Ltd

#1414, Samhuan 8/D, 705-9, Yeoksam-Dong, Gangnam-gu. Seoul 135-080, Korea. Tel: (82) 2562-1592 Fax: (82) 2562-1594

China 中国

Sikoku Kaken (Shanghai) Co. Ltd

Units 3-6, 25F, Far East Building A, No. 319 Xianxia Road, Changning District, Shanghai, China Tel: 86-21-6209-9169 Fax: 86-21-6209-9189

Thailand 泰国

SK Kaken (Thailand) Co. Ltd.

161/1 SG Tower 5th Floor, Soi Mahadlek Luang 3, Ratchadamri Rd, Lumpini, Pathumwan, Bangkok 10330 Thailand. Tel: (66)2-651-8722 Fax: (66)2-651-8721

Vietnam 越南

SKK (S) Vietnam Representative Office

Y Ban Building, Unit #A1, 1th Floor, 69 Thach Thi Thanh St., Dist. 1, HCM City, Vietnam. Tel: (84)8-220-0983 Fax; (84)8-220-0987

India 印度

SKK India Liaison Office

95, V Main, 1B Cross, Domlur 2nd Stage, Bangalore 560 080 India. Tel: (91)80-4148-2831 Fax: (91)80-4148-2836

SK Roadline

Single Pack Chlorinated Rubber Based Paint

RECOMMENDED USE

- Carpark Lines
- Road Marking (i.e. Arrows)



















BLACK



RED



YELLOW

SK EPO Floor

Two Pack Epoxy Floor Coating



RECOMMENDED USE

- Warehouse
- Factories
- Laboratories
- Mechanical Room

EVERGREEN

- Office Floor
- Shops & Restaurants Floor













WHITE EF-9102











SIGNAL RED





EF-9313



MISTY GREY

EXECUTIVE GREY

EF-1457

EF-1461

EF-0104

SK Multi-Floor

Environmental Friendly Water-Based Floor Coating System

RECOMMENDED USE

- Badminton/ Basketball/ Tennis & Other Sport Courts
- Roof Top
- Playground
- Polished Concrete / Asphalt Substrate
- Pedestrian Passway
- Pool Side

CORAL GREY

- Office Floor
- Shop & Restaurant Floor





















APPLE GREEN

BLUE